



Product Specification

Central Diesel provides these specifications as a courtesy and are a guide only. They have been sourced from the manufacturer and may change without notice. Central Diesel accepts no responsibility for any errors or omissions.

Portable generator P5000e



Cummins Portable Generators



Performance you rely on.™

Features and benefits

- 5000 watts running, 5500 watts peak
- 9 hour continuous operating time (at rated load)
- Electric and manual start (battery not included)
- 13 HP, 4-stroke overhead valve engine
- Large 24.6 litre fuel tank
- Automatic "low-oil shutdown"
- Integral battery tray
- Heavy-duty cast iron cylinder sleeve
- Circuit breaker protection
- Dual element air cleaner
- Full perimeter safety frame
- 2 year limited warranty
- Optional wheel kit available
- Stable power via Automatic Voltage Regulation (AVR)
- 12v DC battery charging outlet
- Long range fuel tank with fuel level gauge
- 3 AC power outlets
- Voltmeter
- Includes spark plug spanner and oil fill extension

Weight, size and sound level

- Weight: 84 kg
- Size: Length 680 mm, width 540 mm, height 550 mm
- Sound: 76 dB(A) at 7 m

Application

- General purpose generator ideal for the farm or trade
- Ideal for running multiple power tools or a 140 amp welder or starting up to a 2 hp electric motor

Models and ratings

AC rated output	5 kW	DC amperage	8.3 A
AC max output	5.5 kW	Engine displacement	389 cc
AC voltage	240 V	Engine horsepower	13 HP
AC frequency	50 Hz	Fuel Type	Unleaded petrol
240 V AC rated amperage -	Rated/max	Fuel tank capacity	24.6 L
DC voltage	12 V	Oil capacity	1.1 L

Ratings apply to altitudes up to 1000 ft (304.8 m), 85 °F (30 °C). Total power available will decrease 3.5% for each 1000 ft (304.8 m) above 1000 ft and 2.0% for each 10 °F (5.5 °C) increase in ambient temperature above 85 °F (30 °C).

Cummins® and the "C" logo are servicemarks, trademarks and/or registered trademarks of Cummins Inc. Specifications subject to change without notice.
©2007 Cummins Power Generation. All Rights Reserved.
A-1521 (formerly F-1696) (4/08)