



## Product Specification

Central Diesel provides these specifications as a courtesy and are a guide only. They have been sourced from the manufacturer and may change without notice. Central Diesel accepts no responsibility for any errors or omissions.



# GP30SD

## 30 kVA Silenced Oil Cooled Diesel Generator

### Features

- Original Deutz oil cooled engine
- Original Mecc Alte Alternator
- Remote start controller
- AVR\_s powered from AUX winding
- Noise level of 70 db(A) at 7 meters
- Large fuel tanks (240ltrs)
- Single point lift compact footprint

### Controller Display

- Voltage
- Current
- Frequency
- Battery voltage
- Hour meter
- Fuel level
- Common alarm output available

### Controller Shutdowns

- Low oil pressure
- High temperature
- Low fuel level alarm (shutdown after 5 mins)
- High/Low A/C voltage
- High/Low frequency
- High/Low DC battery voltage
- Belt break shutdown

### SPECIFICATIONS

Standby kVA	30
Standby kW	24
Prime kVA	27
Prime kW	22
Standby Amps	42
Prime Amps	38
Voltage	415
RPM	1500
Engine Model	F4M 201 I
Cylinders	4 In line
Fuel Tank Size	240 ltrs
Fuel Tank Running Time at 75% Load	55 hrs*



Weight	985 kg
Dimensions	2100x900x1170mm
Noise Level @ 7m	70
Other Specifications	Overload: 300% for 20 seconds Alt Brand: Mecc Alte Eco - AVR - 4 pole - Class H - IP21 Fuel Consumption: 6 Engine Brand: Oil-cooled, 4 stroke diesel Service Intervals: 500 Hours Power Factor: 0.8