



Product Specification

Central Diesel provides these specifications as a courtesy and are a guide only. They have been sourced from the manufacturer and may change without notice. Central Diesel accepts no responsibility for any errors or omissions.

Commercial generator series PX12000e



Cummins Portable Generators



Performance you rely on.™

Features and benefits

- 8500 watts running, 10000 watts peak
- 8.7 hour continuous operating time (at rated load)
- Electric start 22 HP, 4-stroke overhead valve engine (battery not included)
- Large 43.2 litre fuel tank
- Volt and hour meter
- High performance alternator w/max surge capacity
- 4 wheel kit including brake
- 2 year limited warranty
- Stable power via Automatic Voltage Regulation (AVR)
- 12v DC battery charging outlet
- Circuit breaker protection
- Automatic "low-oil shutdown"
- Full rollover frame

Weight, size and sound level

- Weight: 329 lbs (149 kg including wheels)
- Size: Length 33 in (838.2 mm), width 30 in (762 mm), height 34 in (863.6 mm)
- Sound: 74.5 dB(A) at 7 m

* Dimensions include wheel kit

Application

- General purpose generator ideal for the farm, trade or back up power
- Runs multiple shearing heads or wool press, up to a 250 amp welder and starts up to a 5 hp electric motor

Models and ratings

AC rated output	8500 VA	DC voltage	12 V
AC max output	10000 VA	Engine horsepower	22.0 HP
AC voltage	240 V	Fuel type	Unleaded petrol
AC frequency	50 Hz	Fuel tank capacity	43.2 L
240 V AC rated amperage -	Rated/max		
	35.4/41.7 A		

Ratings apply to altitudes up to 1000 ft (304.8 m), 85 °F (30 °C). Total power available will decrease 3.5% for each 1000 ft (304.8 m) above 1000 ft and 2.0% for each 10 °F (5.5 °C) increase in ambient temperature above 85 °F (30 °C).